



SOT-23 Plastic-Encapsulate Transistors

S8550LT1 TRANSISTOR (PNP)

FEATURES

Power dissipation

P_{CM} : 0.3 W ($T_{amb}=25^{\circ}C$)

Collector current

I_{CM} : -0.5 A

Collector-base voltage


$V_{(BR)CBO}$: -40 V

Operating and storage junction temperature range

T_J, T_{stg} : -55°C to +150°C

SOT-23

1. BASE
2. Emitter
3. Collector



Unit : mm

ELECTRICAL CHARACTERISTICS ($T_{amb}=25^{\circ}C$)

unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CB}$	$I_C = -100 \mu A, I_E = 0$	-40		V
Collector-emitter breakdown voltage	$V_{(BR)CE}$	$I_C = -0.1mA, I_B = 0$	-25		V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = -100 \mu A, I_C = 0$	-5		V
Collector cut-off current	I_{CBO}	$V_{CB} = -40V, I_E = 0$		-0.1	μA
Collector cut-off current	I_{CEO}	$V_{CE} = -20V, I_B = 0$		-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = -3V, I_C = 0$		-0.1	μA
DC current gain	$H_{FE(1)}$	$V_{CE} = -1V, I_C = -50mA$	120	350	
	$H_{FE(2)}$	$V_{CE} = -1V, I_C = -500mA$	50		
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -500 mA, I_B = -50mA$		-0.6	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = -500 mA, I_B = -50mA$		-1.2	V
Base-emitter voltage	V_{BEF}	$I_E = -100 mA$		-1.4	V
Transition frequency	f_T	$V_{CE} = -6V, I_C = -20mA$ $f = 30MHz$	150		MHz

CLASSIFICATION OF $H_{FE(1)}$

Rank	L	H
Range	120-200	200-350

DEVICE MARKING : S8550LT1=2TY